

Transmisores de conductividad para usar con sonda de cuatro anillos- HI8936-0.0 to 199.9 S/cm- Without LCD

SKU: HI 8936DN

RESUMEN

HI8936 is a conductivity transmitter that utilizes a four-ring potentiometric probe. This probe is virtually immune to contamination by unclean solutions. This allows the transmitter to operate at peak performance at all times.

- Automatic temperature compensation ensures fast, accurately compensated readings even during sudden temperature fluctuations.
- Optional backlit, LCD display for easy viewing.

DESCRIPCIÓN

HI8936 ORP Transmitter FEATURES/BENEFITS:

Easy Installation

- The HI 8936 transmitter may be wall-mounted at any convenient location close to the measurement site. The HI8936 series should be used in conjunction with the HI7635 in-line probe or HI7638 platinum probe.

Automatic Temperature Compensation

- Temperature effects are compensated for by utilizing both the built-in temperature sensor on the probe and the transmitter's ATC circuitry with a of 2%/°C.

Optional LCD

- HI8936"L" versions allow easy verification and monitoring of measured values and is easier to calibrate and maintain.

Direct Probe Connection

- Direct connection of the probe to the transmitter assures a positive electrical connection with no signal loss over long distances.

CARACTERÍSTICAS

Paquete	Frascos goteros
Cantidad	40 pruebas

Método

Método USEPA 425.1 y métodos estándar para el análisis de agua potable y agua residual, 20a edición, 5540C, surfactantes aniónicos como MBAS.

www.hannachile.com Descargado desde: <https://hannachile.com/producto/conductivity-transmitters-to-use-with-four-ring-probe-hi8936-0-0-to-199-9-s-cm-without-lcd/>