

TDS Mini Controller (0.0 to 49.9 ppm) – BL983324-115/230VAC

SKU: BL 983324-1



RESUMEN

The **BL983324** is a compact, panel mounted, process controller for measuring total dissolved solids (TDS) of a process stream that is within the 0.0 to 49.9 ppm (mg/L) range. The device features a large LCD with protective cover. Users may choose from automatic or manual dosing modes. When in automatic mode the dry contact relay is activated when a reading is **above the set point**. The relay can be used to supply power to a dosing pump or a solenoid connected to a valve. The BL983324 can also be used to monitor the quality of water produced from ion exchange, reverse osmosis (RO) or distillation. *The BL983324 uses a 0.5 conversion factor in which $1.0 \text{ ?S/cm} = 0.5 \text{ ppm}$.

Multicolor LED Indicator

LED changes color based on status.

Fire Retardant Casing

For additional safety the controllers outer case is made of fire resistant plastic.

Splash Resistant Cover

A clear plastic cover protects the face panel from dirt and liquids.

DESCRIPCIÓN

HI 324N es un agitador para cargas pesadas que incorpora un control de tiempo , el cual detendrá el motor después de una seleccionada cantidad de tiempo. El tiempo es ajustable desde 5 minutos a 2 horas. Esta característica permite al usuario

ESPECIFICACIONES

tiempo

ACCESORIOS

HI 324N es un agitador para cargas pesadas que incorpora un control de tiempo , el cual detendrá el motor después de una seleccionada cantidad de tiempo. El tiempo es ajustable desde 5 minutos a 2 horas. Esta característica permite al usuario