



TDS Mini Controller (0.0 to 49.9 ppm) – BL983324-115/230VAC

## Description

BL983324 and or type unknown

### Adjustable Dry Contact Dosing Relay

The BL983324 features a dosing relay that is activated when the reading is above a user programmable set point.

### Programmable Overdose Protection

For enhanced safety the mini controller can be programmed to deactivate the dosing relay if the set point is not reached within a specified time interval. The overdosing timer is programmable from 5 to 30 minutes or disabled.

### Relay Control Override

With the flick of a switch the mini controller's relay can be disabled (Off), placed in control (Auto), or be activated for manual operation (On) which is useful for priming a dosing pump.

### Multicolor LED Indicator

Multicolor LED indicator allows an operator to quickly check the status of the controller.

- Green = Meter in measurement mode and reading is below the set point.
- Orange/Yellow = Reading is above the set point and the relay is activated.
- Blinking Red = Indicates an alarm condition such as when the maximum dosing time has been exceeded.

BL983324 and or type unknown

### Fuse Protected Dosing Contacts

The relay dosing contact is rated for up to a 2A load and is fuse protected.

### Labeled Termination Connections

Quick-connect terminal blocks are clearly labeled for easy connection to power, conductivity probe and relay that can be used to operate a dosing pump, valve, audible alarm, or light.

HI7634

Image not found or type unknown

**1/2" NPT Male Threaded Amperometric Probe for Mounting In-line\***

The BL983324 mini controller uses the [HI7634](#) conductivity probe that is available with different cable lengths.

**\*HI7634 is not included and must be ordered separately**

**Especificaciones**

|                                      |   |
|--------------------------------------|---|
| <b>Código</b>                        | BL983324-1  |
| <b>Intervalo de TDS</b>              | 0.0 a 49.9 mg/L (ppm)   |
| <b>Resolución de TDS</b>             | 0.1 mg/L (ppm)  |
| <b>Exactitud de TDS (@25°C/77°F)</b> | ±2% de la escala completa.  |
| <b>Factor de conversión de TDS</b>   | 0.5   |
| <b>Compensación de temperatura</b>   | automática de 5 a 50°C (41 a 122°F) con $\beta=2\%/^{\circ}\text{C}$  |
| <b>Calibración</b>                   | manual, con potenciómetro CAL   |
| <b>Relevador de dosificación</b>     | máximo 2A (protegido por fusible), 250 VCA, 30 VCD, el contacto cierra cuando la medición > punto de ajuste |
| <b>Punto de ajuste</b>               | ajustable de 0 a 49.9 mg/L (ppm)  |
| <b>Tiempo de sobredosificación</b>   | ajustable, típicamente de 5 a aproximadamente 30 minutos  |
| <b>Alimentación eléctrica</b>        | BL983324-0: adaptador de 12 VCD (incluido) BL983324-1: 115/230 VCA; 50/60Hz                                 |
| <b>Dimensiones</b>                   | 83 x 53 x 99 mm (3.3 x 2.1 x 3.9")  |
| <b>Peso</b>                          | BL983324-0: 200 g (7.1 oz.) BL983324-1: 300 g (10.6 oz.)  |
| <b>Información para ordenar</b>      | Se suministra con soportes de montaje, cubierta transparente y manual de instrucciones.                     |
| <b>Sonda recomendada</b>             | Sonda de CE/TDS HI7634-00 con sensor interno de temperatura y 2 m (6.6') de cable (no incluido).            |