



TDS Mini Controller (0.0 to 49.9 ppm) – BL983324-12VDC

Description

BL983324 found or type unknown

Adjustable Dry Contact Dosing Relay

The BL983324 features a dosing relay that is activated when the reading is above a user programmable set point.

Programmable Overdose Protection

For enhanced safety the mini controller can be programmed to deactivate the dosing relay if the set point is not reached within a specified time interval. The overdosing timer is programmable from 5 to 30 minutes or disabled.

Relay Control Override

With the flick of a switch the mini controller's relay can be disabled (Off), placed in control (Auto), or be activated for manual operation (On) which is useful for priming a dosing pump.

Multicolor LED Indicator

Multicolor LED indicator allows an operator to quickly check the status of the controller.

- Green = Meter in measurement mode and reading is below the set point.
- Orange/Yellow = Reading is above the set point and the relay is activated.
- Blinking Red = Indicates an alarm condition such as when the maximum dosing time has been exceeded.

BL983324 found or type unknown

Fuse Protected Dosing Contacts

The relay dosing contact is rated for up to a 2A load and is fuse protected.

Labeled Termination Connections

Quick-connect terminal blocks are clearly labeled for easy connection to power, conductivity probe and relay that can be used to operate a dosing pump, valve, audible alarm, or light.

HI7634 not found or type unknown

1/2" NPT Male Threaded Amperometric Probe for Mounting In-line*

The BL983324 mini controller uses the [HI7634](#) conductivity probe that is available with different cable lengths.

***HI7634 is not included and must be ordered separately**

Especificaciones

Código	BL983324-0
Intervalo de TDS	0.0 a 49.9 mg/L (ppm)
Resolución de TDS	0.1 mg/L (ppm)
Exactitud de TDS (@25°C/77°F)	±2% de la escala completa.
Factor de conversión de TDS	0.5
Compensación de temperatura	automática de 5 a 50°C (41 a 122°F) con $\beta=2\%/^{\circ}\text{C}$

Calibración	manual, con potenciómetro CAL
Relevador de dosificación	máximo 2A (protegido por fusible), 250 VCA, 30 VCD, el contacto cierra cuando la medición > punto de ajuste
Punto de ajuste	ajustable de 0 a 49.9 mg/L (ppm)
Tiempo de sobredosificación	ajustable, típicamente de 5 a aproximadamente 30 minutos
Alimentación eléctrica	BL983324-0: adaptador de 12 VCD (incluido) BL983324-1: 115/230 VCA; 50/60Hz
Dimensiones	83 x 53 x 99 mm (3.3 x 2.1 x 3.9")
Peso	BL983324-0: 200 g (7.1 oz.) BL983324-1: 300 g (10.6 oz.)
Información para ordenar	Se suministra con soportes de montaje, cubierta transparente y manual de instrucciones.
Sonda recomendada	Sonda de CE/TDS HI7634-00 con sensor interno de temperature y 2 m (6.6') de cable (no incluido).