



TDS Mini Controller (0.00 to 10.00 ppt) – BL983318 -115/230VAC

Description

BL983318 found or type unknown

Adjustable Dry Contact Dosing Relay

The BL983318 features a dosing relay that is activated when the reading is above a user programmable set point.

Programmable Overdose Protection

For enhanced safety the mini controller can be programmed to deactivate the dosing relay if the set point is not reached within a specified time interval. The overdosing timer is programmable from 5 to 30 minutes or disabled.

Relay Control Override

With the flick of a switch the mini controller's relay can be disabled (Off), placed in control (Auto), or be activated for manual operation (On) which is useful for priming a dosing pump.

Multicolor LED Indicator

Multicolor LED indicator allows an operator to quickly check the status of the controller.

- Green = Meter in measurement mode and reading is below the set point.
- Orange/Yellow = Reading is above the set point and the relay is active.
- Blinking Red = Indicates an alarm condition such as when the maximum dosing time has been exceeded.

BL983318 found or type unknown

Fuse Protected Dosing Contacts

The relay dosing contact is rated for up to a 2A load and is fuse protected.

Labeled Termination Connections

Quick-connect terminal blocks are clearly labeled for easy connection to power, conductivity probe and relay that can be used to operate a dosing pump, valve, audible alarm, or light.

HI7632 not found or type unknown

1/2" NPT Male Threaded Amperometric Probe for Mounting In-line*

The BL983318 mini controller uses the [HI7632](#) conductivity probe that is available with different cable lengths.

***HI7632 is not included and must be ordered separately**

?

BL9831700 found or type unknown

Front View

Installation cut-out dimensions are provided as well as outside panel dimensions.

BL9831700 found or type unknown

Side View

Adjustable location brackets allow the controller to slide easily and securely into place.

Especificaciones

Código	BL983318
Intervalo de TDS	0.00 a 10.00 g/L (ppt)
Resolución de TDS	0.01 g/L (ppt)
Exactitud de TDS (@25°C/77°F)	±2% de la escala completa
Factor de conversión de TDS	0.5
Compensación de temperatura	automática de 5 a 50°C (41 a 122°F) with $\beta=2\%/^{\circ}\text{C}$
Calibración	manual, con potenciómetro CAL
Relevador de dosificación	máximo 2A (protegido por fusible), 250 Vac, 30 VDC el contacto se cierra cuando la lectura > punto de ajuste
Punto de ajuste	ajustable de 0 a 10 ppt (g/L)
Sobredosificación	ajustable, desde 5 hasta aproximadamente 30 minutos
Alimentación eléctrica	BL983318-0: 12 VCD con adaptador (incluido) BL983318-1: 115/230 VCA; 50/60Hz
Dimensiones	83 x 53 x 99 mm (3.3 x 2.1 x 3.9")
Peso	BL983318-0: 200 g (7.1 oz.) BL983318-1: 300 g (10.6 oz.)
Información para ordenar	Se suministra con accesorios de montaje, cubierta transparente y manual de instrucciones.
Sonda recomendada	HI7632-00 con sensor interno de temperatura y 2 m (6.6') de cable (sonda no incluida)