



TDS Mini Controller (0.00 to 10.00 ppt) – BL983318 -115/230VAC

## Description

BL983318 Sound or type unknown

### Adjustable Dry Contact Dosing Relay

The BL983318 features a dosing relay that is activated when the reading is above a user programmable set point.

### Programmable Overdose Protection

For enhanced safety the mini controller can be programmed to deactivate the dosing relay if the set point is not reached within a specified time interval. The overdosing timer is programmable from 5 to 30 minutes or disabled.

### Relay Control Override

With the flick of a switch the mini controller's relay can be disabled (Off), placed in control (Auto), or be activated for manual operation (On) which is useful for priming a dosing pump.

### Multicolor LED Indicator

Multicolor LED indicator allows an operator to quickly check the status of the controller.

- Green = Meter in measurement mode and reading is below the set point.
- Orange/Yellow = Reading is above the set point and the relay is active.
- Blinking Red = Indicates an alarm condition such as when the maximum dosing time has been exceeded.

BL983318 Sound or type unknown

### Fuse Protected Dosing Contacts

The relay dosing contact is rated for up to a 2A load and is fuse protected.

### Labeled Termination Connections

Quick-connect terminal blocks are clearly labeled for easy connection to power, conductivity probe and relay that can be used to operate a dosing pump, valve, audible alarm, or light.

---

HI7632

Image not found or type unknown

### **1/2" NPT Male Threaded Amperometric Probe for Mounting In-line\***

The BL983318 mini controller uses the [HI7632](#) conductivity probe that is available with different cable lengths.

**\*HI7632 is not included and must be ordered separately**



## Front View

Installation cut-out dimensions are provided as well as outside panel dimensions.

Image not found or type unknown  
BL931700

## Side View

Adjustable location brackets allow the controller to slide easily and securely into place.

### Especificaciones

<b>Código</b>	BL983318
<b>Intervalo de TDS</b>	0.00 a 10.00 g/L (ppt)
<b>Resolución de TDS</b>	0.01 g/L (ppt)
<b>Exactitud de TDS (@25°C/77°F)</b>	±2% de la escala completa
<b>Factor de conversión de TDS</b>	0.5
<b>Compensación de temperatura</b>	automática de 5 a 50°C (41 a 122°F) with $\beta=2\%/^{\circ}\text{C}$
<b>Calibración</b>	manual, con potenciómetro CAL
<b>Relevador de dosificación</b>	máximo 2A (protegido por fusible), 250 Vac, 30 VDC el contacto se cierra cuando la lectura > punto de ajuste
<b>Punto de ajuste</b>	ajustable de 0 a 10 ppt (g/L)
<b>Sobredosificación</b>	ajustable, desde 5 hasta aproximadamente 30 minutos
<b>Alimentación eléctrica</b>	BL983318-0: 12 VCD con adaptador (incluido) BL983318-1: 115/230 VCA; 50/60Hz
<b>Dimensiones</b>	83 x 53 x 99 mm (3.3 x 2.1 x 3.9")
<b>Peso</b>	BL983318-0: 200 g (7.1 oz.) BL983318-1: 300 g (10.6 oz.)
<b>Información para ordenar</b>	Se suministra con accesorios de montaje, cubierta transparente y manual de instrucciones.
<b>Sonda recomendada</b>	HI7632-00 con sensor interno de temperatura y 2 m (6.6') de cable (sonda no incluida)